

SELF-LEVELLING PROFILER

Skid Steer Attachment

The RAMRADE Self-levelling Profiler has been designed for removing the entire layer of asphalt or cement in preparation for trenching or for milling deteriorated sections for later resurfacing.



		Standard Flow	High Flow		High Power		High Depth		
Specifications	Unit	PL35.15	PL45.20	PL60.20	PL1000	PL1200	PL40.35	PL60.25	PL100.25
Standard Drum Width	mm	350	450	600	1000	1200	400	600	1000
Standard Drum Depth	mm	0-110	0-150	0-170	0-130	0-130	100-350	0-250	0-250
Self Levelling Angle	Degrees	30	30	30	30	30	26	26	26
Side Shift		Mech or Hyd	Hyd	Hyd	Hyd	Hyd	Hyd	Hyd	Hyd
Tilt		Option	Auto/Hyd	Auto/Hyd	Auto/Hyd	Auto/Hyd	Auto/Hyd	Auto/Hyd	Auto/Hyd
Inclination	Degrees	16	16	16	16	16	16	16	16
Oil Pressure Range	Bar	160-240	160-300	160-300	180-350	180-350	180-320	180-300	180-350
	PSI	2320-3480	2320-4351	2320-4351	2610-5076	2610-5076	2610-4641	2320-4351	2610-5076
Recommended Oil Flow	LPM	45-75	65-140	90-160	95-200	110-200	90-180	90-160	95-200
Weight	Kg	590-850	790-940	950-1100	1090-1200	1210-1320	1150-1270	1200-1350	1650-1760

KEY FEATURES

- Optional Dust Prevention Water System Either
- Mounted or Integrated to the Side Shift Frame
- Excellent Retention of Milled Material
- Independent Left and Right Adjust
- Self-Leveling and Constant Planing Depth
- High Visibility for the Operator
- Optional Drum Widths and Teeth Layout Available for Different Surfaces