

# VIBRATING COMPACTION WHEEL

## Skid Steer Attachment

The RAMRADE Vibrating Compaction Wheel has been designed for compacting trench beds to guarantee a permanently firm, even and well compacted bed and ensure road safety.



Specifications	Unit	CT 2.8 Standard	CT 2.8 F.O.
<b>Standard Wheel</b>			
<b>Width of Bolted Sectors</b>	mm	200 - 250 - 300 - 350 - 400	200 - 250 - 300 - 350 - 400
<b>Working Depth</b>	mm	0 - 700	0 - 700
<b>Special Wheels</b>			
<b>Wheel Widths <sup>(1)</sup></b>	mm	50 - 100 - 150	50 - 100 - 150
<b>Working Depth</b>	mm	0 - 350	0 - 350
<b>Vibration Frequency</b>	Hz	30 - 40	30 - 40
<b>Max. Vertical Force</b>	kN	42	42
<b>Hydrostatic Side Shift</b>	mm	-	1100
<b>Hydraulic Transverse Tilt</b>		-	18°
<b>Operating Weight <sup>(2)</sup></b>	Kg	710 - 770	910 - 970
<b>Required Oil Flow</b>	L/min	40 - 50	50 - 70
<b>Required Oil Pressure</b>	BAR	150 - 220	150 - 220

(1) Widths different from those indicated are available on request.

(2) User is responsible for ensuring that the equipment meets the excavator's specifications and weight requirements.

### KEY FEATURES

- Reverse-Rotation Vibrating Twin Shaft
- Adjustable Wheel Width
- Full Optimal Option Permits Lateral Extension
- Outside of the Wheel Prime Mover for Working in Tight Spaces
- Easily Replaceable Sectors