

ROTARY DRUM CRUSHER

Excavator Attachment

The RAMRADE Drum Crusher is ideal for trenching hard materials, profiling and resurfacing rock and cement walls, quarrying, demolitions and dredging.



Specifications	Unit	TF200	TF400	TF600	TF850	TF1100	TF2100	TF2500	TF3100
Machine Size	Tonne	2.5 - 7	6 - 12	9 - 16	14 - 22	20 - 34	28 - 45	40 - 55	50 - 70
Standard Drum width	mm	565	625	700	800	850	950	1000	1250
Standard Drum diameter	mm	380	450	500	595	660	750	750	750
Weight (without bracket)	Kg	300	470	640	1140	1465	2410	2700	3650
Recommended oil flow	LPM	45 - 80	65 - 120	90 - 150	130 - 190	170 - 250	240 - 340	280 - 400	350 - 500
Maximum operating pressure	Bar	350	350	350	350	350	380	380	380
	PSI	5076	5076	5076	5076	5076	5511	5511	5511

KEY FEATURES

- Low Noise, Can Work Close to Houses, Hospitals, Schools etc.
- Ideal for Flat, Horizontal or Vertical Faces
- Low Vibrations
- Replaceable Anti-Wear Plates
- High Torque and High Performance
- Multiple Different Teeth Options Available for Milling Different Surfaces