

NORM ENGINEERING GRAPPLE BUCKET

Skid Steer Attachment

The Norm Engineering Concrete Bucket has been designed for small batch concreting and is ideal for remote locations where pre-mixed concrete isn't readily available.



Specifications	Weight (kg)	Width (mm)	Depth (mm)	Height (mm)	Capacity (m3)
Sieve Grapple Bucket (1650mm)	412	1650	730	920	0.38
Sieve Grapple Bucket (1750mm)	424	1750	730	920	0.4
Sieve Grapple Bucket (1880mm)	484	1880	730	920	0.43
Sieve Grapple Bucket (2000mm)	499	2000	730	920	0.46
Sieve Grapple Bucket (2150mm)	517	2150	730	920	0.49
Demolition Grapple Bucket (1650mm)	363	1650	730	920	0.47
Demolition Grapple Bucket (1750mm)	372	1750	730	920	0.49
Demolition Grapple Bucket (1880mm)	420	1880	730	920	0.48
Demolition Grapple Bucket (2000mm)	433	2000	730	920	0.51
Demolition Grapple Bucket (2150mm)	447	2150	730	920	0.55

KEY FEATURES

- Hydraulic Operated Grapples
- Independent Operated Grapple Arms to Accommodate Uneven Loads
- Flat Floor and Sieve Floor Options Available
- High Strength Design - Weld On Edge for Extra Strength
- Low Maintenance Greasable Pivot System