

MULCHER

Excavator Attachment

The Mulcher attachment is ideal for fire prevention, bushfire clean up, land clearing and general vegetation management and is available in various sizes and fixed and swinging head options.



Specifications	Unit	PML/HY 90	PMM/HY 125	PML/EX 100	PML/EX 125	BL1/EX 75	BL2/EX 100	BL2/EX 120
Excavator Weight	Tonne	2.5 – 3.5	4.5 – 5.5	5.5 – 7.5	6.0 – 7.5	4 – 7.5	8 – 14	
Flow Rate	LPM	16 – 20	25 – 40	25 – 40		50 – 130	100 – 140	
Pressure	Bar	150 – 210	150 – 210	150 – 210		180 – 350	180 – 350	
Working Width	mm	90	1495	1015	1255	800	1000	1240
Weight	kg	210	330	320	400	355	320	400
Max Shredding Diameter	mm	40	50	60		120	150	
No Teeth Hammer/ Flails	qty	14/14	24/24	16/16	20/20	14	18	22

KEY FEATURES

- Flow Control System Valve
- Safety and Anticavitation Valve
- Motor Enclosed in the Frame
- Belt Transmission
- Bulkhead for Hydraulic Connections
- Front Hood with Mechanical Adjustment