

ROBI DEMOLITION GRAB

The Robi DG16RD Demolition Grab is a versatile and robust attachment designed for efficient demolition, sorting, and loading tasks, particularly suited for structures composed of brick and wood.

KEY FEATURES

- Built from durable, high-quality materials
- Features unique double dog bone mechanism
- Wide bearing ensures longer, reliable performance
- Ideal for demolition, sorting, and loading
- Quick to attach and easy to use
- Precise handling enhances safety and control



	Unit	DG11R	DG16RD	DG21RD	DG31RD
Carrier weight	tonne	Custom Built	Custom Built	Custom Built	Custom Built
Weight	kg	12 - 20	16 - 25	20 - 30	26 - 35
Lifting capacity	kg	1,029	1,539	1,799	2,461
Max opening	mm	80 - 140	100 - 150	130 - 180	170 - 240
Device height	mm	105	125	135	150
Closing force	kN	140 - 180	160 - 180	160 - 180	165 - 185
Volume, jaws closed	L	550 - 850	440 - 700	430 - 650	400 - 680
Cylinder max	bar/l/min	380 - 700	340 - 550	330 - 500	310 - 490
Rotation (1 motor) max	bar/l/min	2,150	2,800	3,200	4,200
Rotation (2 motor) max	bar/l/min	2,500	3,500	4,300	6,100